

RD-R169 543

1983-84 CONNECTICUT 45-HZ-BAND FIELD-STRENGTH
MEASUREMENTS(U) NAVAL UNDERWATER SYSTEMS CENTER NEW
LONDON CT NEW LONDON LAB P R BANNISTER 07 MAR 86


1/1


UNCLASSIFIED

NUSC-TR-7519

F/G 20/14

NL





MICROCOPY RESOLUTION TEST CHART
NATIONAL BUREAU OF STANDARDS - 1963 - A

15

✓

NUSC-Technical Report 7519
7 March 1986

1983-84 Connecticut 45-Hz-Band Field-Strength Measurements

Peter R. Bannister
Submarine Electromagnetic Systems Department

AD-A169 543



Naval Underwater Systems Center
Newport, Rhode Island / New London, Connecticut

DTIC FILE COPY

DTIC
ELECTED
JUL 17 1986
S D
A B

Approved for public release; distribution unlimited.

Preface

This report was prepared under NUSC Project No. A59007, "ELF Propagation RDT&E" (U), Principal Investigator, P. R. Bannister (Code 3411), Navy Program Element No. 1140IN and Project No. XD792, Space and Naval Warfare Systems Command (SPAWARSCOM), Capt. R. Koontz (Code PDW 110-3), Program Manager ELF Communications.

The Technical Reviewer for this report was Raymond F. Ingram, (Code 3411).

Reviewed and Approved: 7 March 1986



D. F. Dence
Head, Submarine Electromagnetic
Systems Department

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE

AD-A169543


REPORT DOCUMENTATION PAGE

1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED		1b. RESTRICTIVE MARKINGS										
2a. SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution is unlimited.										
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE												
4. PERFORMING ORGANIZATION REPORT NUMBER(S) TR 7519		5. MONITORING ORGANIZATION REPORT NUMBER(S)										
6a. NAME OF PERFORMING ORGANIZATION Naval Underwater Systems Center	6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION										
6c. ADDRESS (City, State, and ZIP Code). New London Laboratory New London, CT 06320		7b. ADDRESS (City, State, and ZIP Code)										
8a. NAME OF FUNDING/SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER										
8c. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF FUNDING NUMBERS PROGRAM ELEMENT NO. PROJECT NO. TASK NO. WORK UNIT ACCESSION NO.										
11. TITLE (Include Security Classification) 1983-84 CONNECTICUT 45-Hz-BAND FIELD-STRENGTH MEASUREMENTS												
12. PERSONAL AUTHOR(S) Peter R. Bannister												
13a. TYPE OF REPORT	13b. TIME COVERED FROM _____ TO _____	14. DATE OF REPORT (Year, Month, Day) 86/3/7	15. PAGE COUNT									
16. SUPPLEMENTARY NOTATION												
17. COSATI CODES <table border="1"><tr><th>FIELD</th><th>GROUP</th><th>SUB-GROUP</th></tr><tr><td> </td><td> </td><td> </td></tr><tr><td> </td><td> </td><td> </td></tr></table>		FIELD	GROUP	SUB-GROUP							18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB-GROUP										
19. ABSTRACT (Continue on reverse if necessary and identify by block number) (U) The results of 23 days of 45-Hz-band Connecticut measurements taken during 1983-84 are discussed in this report. The main result is that the average measured field strengths are in excellent agreement (in both amplitude and relative phase) with previous 45-Hz-band measurement results.												
20. DISTRIBUTION/AVAILABILITY OF ABSTRACT <input type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT. <input type="checkbox"/> DTIC USERS		21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED										
22a. NAME OF RESPONSIBLE INDIVIDUAL Peter R. Bannister		22b. TELEPHONE (Include Area Code) (203) 440-4885	22c. OFFICE SYMBOL Code 5411									

TABLE OF CONTENTS

	Page
LIST OF ILLUSTRATIONS	ii
LIST OF TABLES	ii
INTRODUCTION	1
THEORY	2
PAST 45-Hz-BAND RESULTS	5
1983-84 45-Hz-BAND MEASUREMENTS	7
CONCLUSIONS	9
REFERENCES	18

S DTIC
ELECTED
JUL 17 1986 D
B



LIST OF ILLUSTRATIONS

Figure		Page
1	Magnitude of H_ϕ Versus Range ($f = 45$ Hz, WTF Omni)	10
2	Magnitude of H_ϕ Versus Range ($f = 75$ Hz, WTF Omni)	11
3	Connecticut 44-Hz Field Strength Versus GMT, 16 Through 18 December 1983 (Normalized to $I = 300$ A and $\psi = 291$ deg)	12
4	Connecticut 44-Hz Field Strength Versus GMT, 17 Through 19 March 1984 ($\psi = 291$ deg, $I = 300$ A)	13
5	Connecticut 44-Hz Field Strength Versus GMT, 15 Through 17 September 1984 ($\psi = 291$ deg, $I = 300$ A)	14
6	Connecticut 42-Hz Field Strength Versus GMT, 6 Through 8 October 1984 ($\psi = 291$ deg, $I = 300$ A)	15
7	Connecticut 44-Hz Field Strength Versus GMT, 13 Through 15 October 1984 ($\psi = 291$ deg, $I = 300$ A)	16
8	Connecticut 46-Hz Field Strength Versus GMT, 27 Through 29 October 1984 ($\psi = 291$ deg, $I = 300$ A)	17

LIST OF TABLES

Table		Page
1	1970-72 45-Hz-Band Ambient Daytime Interpretations	5
2	1970-72 45-Hz-Band Ambient Nighttime Interpretations	6
3	January 1983 44-Hz Daytime Connecticut Field-Strength Averages (Normalized to $I = 300$ A and $\psi = 291$ deg)	7
4	45-Hz-Band Connecticut Field-Strength Averages (Normalized to $I = 300$ A and $\psi = 291$ deg)	8

1983-84 CONNECTICUT 45-Hz-BAND FIELD-STRENGTH MEASUREMENTS

INTRODUCTION

Since June 1970, we have made extremely low frequency (ELF) measurements of the transverse horizontal magnetic field strength (H_ϕ) received in Connecticut.¹⁻¹⁵ The local measurement site from June 1970 to October 1971 was in the Nehantic State Forest, East Lyme, CT. From October 1971 through November 1975, it was located in Hammonassett State Park, Madison, CT. Since July 1976, the AN/BSR-1 ELF receiver has been located at the Naval Underwater Systems Center (NUSC), at New London, CT. The loop receiving antenna is now located at Fishers Island, NY (about 10 km from New London). The receiver and receiving antenna are connected by means of a microwave link from Fishers Island to New London.

The AN/BSR-1 receiver is composed of an AN/UYK-20 minicomputer, a signal timing and interface unit (STIU), a rubidium frequency time standard, two magnetic-tape recorders, and a preamplifier.

The transmission source for these farfield (1.6-Mm range) measurements is the U.S. Navy's ELF Wisconsin Test Facility (WTF), located in the Chequamegon National Forest in north-central Wisconsin, about 8 km south of the village of Clam Lake. The WTF consists of two 22.5-km antennas; one antenna is located approximately in the north-south (NS) direction and one is located approximately in the east-west (EW) direction. Each antenna is grounded at both ends. The electrical axis of the WTF EW antenna is 118 deg east of north at 45 Hz and 114 deg east of north at 75 Hz. The electrical axis of the WTF NS antenna is 11 deg east of north at 45 Hz and 14 deg east of north at 75 Hz. The WTF array can be steered electrically toward any particular location. Its radiated power is approximately 0.5 W at 45 Hz and 1 W at 75 Hz.

Since July 1976, nearly all of the Connecticut field-strength measurements have been taken at a WTF transmitting frequency of 76 ± 4 Hz.⁵⁻¹⁵ In this report we will discuss the results of the limited amount of 45-Hz-band data taken during 1983-84 and compare them with previous 45-Hz-band measurement results.

THEORY

For measurement distances greater than $1.5L$ and greater than an earth wavelength, λ_e , the (direct path) H_ϕ component produced by the WTF EW antenna (of length L) can be expressed as^{16,17}

$$H_\phi \sim -\frac{ILf(L)G(t)\cos \phi e^{-\alpha\rho}}{2\pi Y_e \rho^3} \left[\left(-\frac{i\pi x}{2} \right) H_1^{(2)}(x) f(x) S \right] \text{ A/m ,} \quad (1)$$

where

I = WTF EW antenna current (300 A),

L = WTF EW antenna length (2.25×10^4 m),

ϕ = azimuth angle (deg),

ρ = great-circle distance between WTF and receiver (m),

h = effective ionospheric reflecting height (m),

α = earth-ionosphere waveguide attenuation rate (Np/m),

v = earth-ionosphere waveguide phase velocity (m/s),

c = velocity of light in free space ($\sim 3 \times 10^8$ m/s),

S = spherical earth spreading factor,

a = radius of the earth ($\sim 6.37 \times 10^6$ m),

$\gamma_e \approx (i\omega\mu_0\sigma_e)^{1/2} = (1 + i)/\delta_e \approx$ propagation constant in the earth beneath the WTF EW antenna (meters⁻¹),

$\delta_e \approx \sqrt{2/(\omega\mu_0\sigma_e)}$ = skin depth in the earth beneath the WTF EW antenna (m),

$\lambda_e = 2\pi\delta_e$ = wavelength in the earth (m),

σ_e = effective conductivity beneath the WTF EW antenna (2.8×10^{-4} S/m at 45 Hz and 3.2×10^{-4} S/m at 75 Hz),

$H_1^{(-)}(x)$ = Hankel function of the second kind, order zero, and argument x , and

$H_1^{(+)}(x)$ = Hankel function of the second kind, order one, and argument x .

For $\rho \leq 2$ Mm, the spherical earth spreading factor $S = 1$. For $2 \leq \rho \leq 19$ Mm,

$$S = \sqrt{\frac{\rho/a}{\sin(\rho/a)}} , \quad (2)$$

while, at the antipode ($\rho = \pi a = 20$ Mm),^{18,19}

$$S = \sqrt{\frac{\pi x}{2}} , \quad (3)$$

where

$$x = k\rho(c/v) = \frac{2\pi\rho}{\lambda}(c/v) . \quad (4)$$

The functions $f(L)$, $f(x)$, and $G(t)$ are defined by

$$f(L) = 1 + 2\left(\frac{L}{2\rho}\right)^2\left(1 - \frac{15}{4}\sin^2\phi\right) , \quad (5)$$

$$f(x) = 1 - x\left(\frac{H_0^{(2)}(x)}{H_1^{(2)}(x)}\right) , \quad (6)$$

and

$$G(t) = \left(\frac{2t}{\pi}\right)\coth t + \left(1 - \frac{2}{\pi}\right)t^2 \operatorname{csch}^2 t , \quad (7)$$

where

$$t = \frac{\pi\rho}{2h(c/v)} . \quad (8)$$

When $t < 0.5$, $G(t) \sim 1$. When $t > 2.5$, $G(t) \sim 2t/\pi$, $x \gg L$, and $f(L) \sim 1$. Therefore, when $t > 2.5$, equation (1) reduces to

$$H_\phi \sim -\frac{IL \cos \phi e^{-\alpha\rho}}{2\pi\gamma_e h(c/v)^2 \rho^2} \left[\left(-\frac{i\pi x}{2}\right) H_1^{(2)}(x) f(x) S \right] \text{ A/m} . \quad (9)$$

When $x > 1.6$ (approximately 1.4 Mm at 45 Hz and 0.85 Mm at 75 Hz¹⁶),

$$\left[\left(-\frac{i\pi x}{2}\right) H_1^{(2)}(x) f(x) \right] \sim ix\sqrt{\frac{\pi x}{2}} e^{-i(x-\pi/4)} \quad (10)$$

and equation (9) reduces to

$$H_\phi \sim -\frac{ILS \cos \phi e^{-\alpha\rho}}{2\pi\gamma_e h(c/v)^2 \rho^2} ix\sqrt{\frac{\pi x}{2}} e^{-i(x-\pi/4)} \text{ A/m} . \quad (11)$$

Furthermore, when $x > 1.6$, but $\rho \leq 19$ Mm, equation (11) becomes

$$H_\phi \sim -\frac{\pi IL \cos \phi e^{-\alpha\rho}}{\gamma_e h^{3/2} (c/v)^{1/2}} \left(\frac{e^{-i(x-\pi/4)}}{\sqrt{a \sin(\pi/2/a)}} \right) \text{ A/m} , \quad (12)$$

while, at the antipode ($\phi = \pi a$), the magnitude of H_ϕ is equal to (from equation (11))

$$|H_\phi| \sim \frac{\pi^2 IL(\delta_e/\sqrt{2}) \cos \phi e^{-2\pi a}}{h\lambda^2} \text{ A/m .} \quad (13)$$

The direct path H_ϕ component produced by the WTF antenna array can be obtained from equations (1), (9), (11), (12), or (13) by replacing $\cos \phi$ with $F(\phi)/B$, the WTF array pattern factor^{6,20} (which equals unity in the direction of the EW antenna axis). For $x > 1.6$ and $\phi \leq 19$ Mm, the direct-path H_ϕ component produced by the WTF antenna array (equation (12)) also can be expressed as

$$\begin{aligned} 20 \log H_\phi \sim K + 20 \log E - \alpha \rho - 10 \log \left[a \sin \left(\frac{\rho}{a} \right) \right] \\ + 20 \log \left(\frac{F(\phi)}{B} \right) \text{ dBA/m ,} \end{aligned} \quad (14)$$

where $K = -143.7$ dB at 45 Hz and -139.2 dB at 75 Hz and

$$E = \left(h_{KM} \sqrt{\sigma_e} \sqrt{c/v} \right)^{-1}$$

is defined as the earth-ionosphere waveguide excitation factor. In equation (14), h is in km, ρ and a are in Mm, and α is in dB/Mm.

Plotted in figures 1* and 2 versus range are predicted 45-Hz and 75-Hz values of the direct path H_ϕ component produced by the omnidirectionally-phased (omni) WTF array ($20 \log F(\phi)/B \sim +0.8$ dB) during daytime, transition period (TP), and nighttime propagation conditions. Equations (13) and (14) and the all-paths average values of attenuation rates and excitation factors²¹ were used for these predictions. Note that the predicted antipodal field strengths are approximately equal to the 7- to 9-Mm field strengths at 45 Hz and the 8- to 11-Mm field strengths at 75 Hz (depending on propagation conditions). Also, there is a crossover point (approximately 6 Mm at 75 Hz and 11 Mm at 45 Hz) where the predicted field strengths are identical during daytime, transition period, and nighttime propagation conditions.

For distances from approximately 5 to 20 Mm (depending on frequency and propagation conditions), there also will be a standing-wave pattern set up due to interference between the direct (short-path) and "round-the-world" (long-path) field-strength components.

*All figures have been placed together at the end of this report.

PAST 45-Hz-BAND RESULTS

Presented in tables 1 and 2 are summaries of the 45-Hz-band interpretations for ambient daytime and nighttime propagation conditions.²¹ The values of the attenuation rate and excitation factor were inferred from the limited propagation measurements taken over various paths from 1970 through 1972.²² The average daytime and nighttime attenuation rates inferred from these measurements were 1.03 and 0.74 dB/Mm, respectively, while the excitation factors were +0.7 dB during the day and -2.5 dB at night.

A convenient quantity to describe the characteristics of the lower ionosphere is the conductivity parameter ω_r , which is defined by

$$\omega_r = \omega_0^2/v , \quad (15)$$

where ω_0 is the (angular) plasma frequency of the electrons and v is the effective collision frequency.²³ The plasma frequency at a particular height is determined directly by the electron-density profile. Experience has shown that simple exponential models of the electron density and collision frequency in the lower ionosphere are adequate to describe extremely low frequency/very low frequency/low frequency (ELF/VLF/LF) radiowave propagation in most cases. The exponential height profile of the conductivity parameter ω_r successfully employed by Wait and Spies²⁴ is

$$\omega_r(z) = 2.5 \times 10^5 \exp[-\beta(H - z)] , \quad (16)$$

where β is equal to $1/\zeta$, ζ is the scale height, and H is the (arbitrary) reference height.

Table 1. 1970-72 45-Hz-Band Ambient Daytime Interpretations

Path	Date	α_D (dB/Mm)	E_D (dB)	c/v	h (km)	ζ (km)	β (km ⁻¹)	H (km)
California/Hawaii	7/70	1.20	1.4	1.37	43.6	3.88	0.26	70.0
Utah/Hawaii	3/71-4/71	1.20	1.4	1.37	43.6	3.88	0.26	70.0
North Carolina/ Virgin Islands	3/71-4/71	1.10	0.9	1.54	46.4	3.80	0.26	72.2
All Sites/Norway	10/71-11/71	0.90	1.1	1.50	46.4	5.15	0.52	67.6
Alaska/Saipan	5/72	0.90	0.0	1.29	52.5	3.55	0.28	76.6
WTF/Greece	5/72	0.80	0.0	1.27	53.0	5.20	0.31	74.7
WTF/Norway	5/72	1.00	0.0	1.32	52.0	5.89	0.26	78.4
Averages		1.03	+0.7	1.32	48.2	5.62	0.28	72.8

Table 2. 1970-72 45-Hz-Band Ambient Nighttime Interpretations

Path	Date	α_N (dB/Mm)	E_N (dB)	c/v	h (km)	ζ (km)	β (km $^{-1}$)	H (km)	h_E (km)
California/Hawaii	7/70	0.7	-3.3	1.13	82.3	3.00	0.33	102.6	104.7
Utah/Hawaii	3/71-4/71	0.8	-2.3	1.15	72.8	3.04	0.33	93.4	95.5
North Carolina/Virgin Islands	3/71-4/71	0.8	-2.2	1.15	72.0	3.00	0.33	92.3	94.4
All Sites/Norway	10/71-11/71	0.9	-0.1	1.16	56.1	2.63	0.38	73.9	75.7
Alaska/Saipan	5/72	0.7	-3.3	1.13	82.3	3.00	0.33	102.6	104.7
WTF/Greece	5/72	0.6	-3.3	1.11	82.9	2.59	0.39	100.5	102.3
WTF/Greece	5/72	0.7	-3.3	1.13	82.3	3.00	0.33	102.6	104.7
Averages		0.74	-2.5	1.14	75.8	2.89	0.35	95.4	97.4

Also included in tables 1 and 2 are representative ionospheric parameters for each propagation path considered.²¹ These parameters include the reflection height h , scale height ζ , inverse scale height β , and reference height H . For nighttime propagation (table 2), the height of the E-layer (h_E) also is included.²¹

For ambient daytime conditions, the individual path variations in the reflection height, inverse scale height, and the reference height of the equivalent exponential ionosphere profile were 43 to 53 km, 0.26 to 0.32 km^{-1} , and 67 to 78 km, respectively.

For ambient nighttime propagation conditions, the individual path variations in h , β , and H were 56 to 83 km, 0.33 to 0.39 km^{-1} , and 74 to 103 km, respectively.

1983-84 45-Hz-BAND MEASUREMENTS

During 1983 and 1984, reliable field-strength data were obtained on 23 days at the Connecticut site. The daily plots of signal strength (both amplitude and relative phase) versus Greenwich Mean Time (GMT) (in 1-hr increments) are presented in figures 3 through 8, while the daily field-strength averages are presented in tables 3 and 4. These data are broken up into four time periods, which are representative of nighttime, sunrise transition period (SRTP), daytime, and sunset transition period (SSTP) propagation conditions. The data are all normalized to a WTF antenna current of 300 A and an array phasing angle of 291 deg.

Referring to tables 1 and 2, we see that the average daytime and nighttime attenuation rates inferred from the 1970-72 45-Hz-band measurements were 1.05 and 0.74 dB/Mm , respectively, while the excitation factors were $+0.7 \text{ dB}$.

Table 3. January 1983 44-Hz Daytime Connecticut Field-Strength Averages (Normalized to $I = 300 \text{ A}$ and $\varphi = 291 \text{ deg}$)

Date	H_{ζ} (dBA/m)
1/10/83	-145.6
1/11/83	-145.7
1/12/83	-145.6
1/13/83	-145.9
1/14/83	-146.8
1/83 Average	-145.9
Predicted 44-Hz Average	-145.9

Table 4. 45-Hz-Band Connecticut Field-Strength Averages
(Normalized to I = 300 A and ψ = 291 deg)

Frequency (Hz)	Date	Night H _φ (dBA/m)	SRTP H _φ (dBA/m)	Day H _φ (dBA/m)	SSTP H _φ (dBA/m)	$\Delta\phi$ (deg)
44	12/16/83	-149.0	-147.5	-146.5(1)	-	10.4
44	12/17/83	-149.1	-147.8	-146.1	-147.1	9.7
44	12/18/83	-148.5	-147.8	-146.0	-146.8	5.0
44	Averages	-148.9	-147.7	-146.1	-146.9	8.4
44	3/17/84	-148.7	-147.6	-146.3	-147.6	11.8
44	3/18/84	-149.2	-147.2	-145.9	-147.2	23.6
44	3/19/84	-148.9	-147.1	-145.9	-147.0	16.8
44	Averages	-148.9	-147.3	-146.1	-147.2	17.4
44	9/15/84	-148.6	-147.6	-145.9	-146.4	17.3
44	9/16/84	-148.2	-148.6	-145.9	-146.5	18.3
44	9/17/84	-148.8	-148.4	-	-148.1	6.3
44	Averages	-148.5	-148.2	-145.9	-147.0	14.0
42	10/6/84	-149.1	-148.1	-146.3	-147.8	16.5
42	10/7/84	-148.5	-147.6	-146.7	-147.3	-1.0
42	10/8/84	-149.2	-147.7	-	-	28.0
42	Averages	-148.9	-147.8	-146.5	-147.5	14.5
44	10/15/84	-148.6	-147.3	-146.0	-148.1	24.5
44	10/14/84	-149.0	-147.7	-146.2	-147.2	17.0
44	10/15/84	-148.5	-148.0(2)	-	-	13.8
44	Averages	-148.7	-147.6	-146.1	-147.6	18.4
46	10/27/84	-148.4	-146.6	-145.7	-147.2	15.4
46	10/28/84	-148.1	-147.1	-146.0	-147.5	19.5
46	10/29/84	-148.2	-147.1	-	-	11.8
46	Averages	-148.2	-146.9	-145.8	-147.5	15.6
Averages, Normalized (to 44 Hz)		-148.6	-147.5	-146.0	-147.2	14.7
Predicted 44-Hz Averages		-148.6	-147.3	-145.9	-147.5	15.2

during the day and -2.5 dB at night. Inserting these values in equation (14) results in predicted 44-Hz Connecticut average field strengths of -145.9 dBA/m during the day, -147.3 dBA/m during the transition periods, and -148.6 dBA/m at night. Referring to tables 3 and 4, we see that the predicted and measured 44-Hz average field strengths are almost identical.

The average 1983-84 night-to-day relative-phase variation ($\Delta\phi$) was 14.7 deg (table 4). This corresponds to an average difference in the night-to-day relative-phase velocity ratio ($\Delta(c/v)$) of 0.174, which is almost identical to the 0.18 average value (1.32 - 1.14) inferred from the 1970-72 measurements.

CONCLUSIONS

In this report, we have presented the results of 23 days of 45-Hz-band Connecticut measurements taken during 1983-84. We have shown that the average measured field strengths were in excellent agreement with previous 45-Hz-band measurement results during daytime, transition period, and nighttime propagation conditions.

The average night-to-day relative-phase variation was 14.7 deg. This corresponds to an average difference in the night-to-day relative-phase velocity ratio of 0.174, which is almost identical to the previously inferred value of 0.18.





Figure 1. Magnitude of H_ϕ Versus Range ($f = 45$ Hz, WTF Omni)

Figure 2. Magnitude of H_ϕ Versus Range ($f = 75$ Hz, WTF Omni)




Figure 3. Connecticut 44-Hz Field Strength Versus GMT, 16 Through 18 December 1983 (Normalized to $I = 500$ A and $\phi = 291$ deg)




Figure 4. Connecticut 44-Hz Field Strength Versus GMT, 17 Through 19 March 1984 ($L = 291$ deg, $I = 300$ A)




Figure 5. Connecticut 44-Hz Field Strength Versus GMT, 15 Through 17 September 1984 (. = 291 deg, I = 300 A)




Figure 6. Connecticut 42-Hz Field Strength Versus GMT, 6 Through 8 October 1984 ($\phi = 291$ deg, $I = 300$ A)

TR 7519




Figure 7. Connecticut 44-Hz Field Strength Versus GMT, 13 Through 15 October 1984 ($\omega = 291$ deg, $I = 300$ A)




Figure 8. Connecticut 46-Hz Field Strength Versus GMT, 27 Through 29 October 1984 ($\omega = 291$ deg, $I = 500$ A)

REFERENCES

1. P. R. Bannister, F. J. Williams, J. R. Katan, and R. F. Ingram, Results of ELF Farfield Measurements Made in Connecticut, June 1970 - May 1973, NUSC Technical Report 4617, Naval Underwater Systems Center, New London, CT, 17 October 1973.
2. P. R. Bannister and F. J. Williams, ELF Field Strength Measurements Made in Connecticut from September 1973 through January 1974, NUSC Technical Report 4791, Naval Underwater Systems Center, New London, CT, 6 May 1974.
3. P. R. Bannister and F. J. Williams, ELF Field Strength Measurements Made in Connecticut During 1974, NUSC Technical Report 4927, Naval Underwater Systems Center, New London, CT, 1 October 1975.
4. P. R. Bannister and F. J. Williams, ELF Field Strength Measurements Made in Connecticut During 1975, NUSC Technical Report 5695, Naval Underwater Systems Center, New London, CT, 15 August 1977.
5. P. R. Bannister, ELF Field Strength Measurements Made in Connecticut During 1976, NUSC Technical Report 5853, Naval Underwater Systems Center, New London, CT, 11 September 1978.
6. P. R. Bannister et al., "Extremely Low Frequency (ELF) Propagation," NUSC Scientific and Engineering Studies, Naval Underwater Systems Center, New London, CT, February 1980, 550 pp.
7. P. R. Bannister, ELF PVS Field Strength Measurements, January 1977, NUSC Technical Report 6879, Naval Underwater Systems Center, New London, CT, 1 March 1983.
8. P. R. Bannister, ELF PVS Field Strength Measurements, March 1977, NUSC Technical Report 6769, Naval Underwater Systems Center, New London, CT, 3 February 1983.
9. P. R. Bannister, ELF PVS Field Strength Measurements, April 1977, NUSC Technical Report 6771, Naval Underwater Systems Center, New London, CT, 3 February 1983.
10. P. R. Bannister, ELF PVS Field Strength Measurements, October 1977, NUSC Technical Report 6773, Naval Underwater Systems Center, New London, CT, 3 February 1983.
11. P. R. Bannister, ELF PVS Field Strength Measurements, January/February 1978, NUSC Technical Report 6775, Naval Underwater Systems Center, New London, CT, 3 February 1983.
12. P. R. Bannister, Connecticut ELF Field Strength Measurements, May to July 1977, NUSC Technical Report 6887, Naval Underwater Systems Center, New London, CT, 11 January 1984.

13. P. R. Bannister, Connecticut ELF Field Strength Measurements, March to May 1978, NUSC Technical Report 7079, Naval Underwater Systems Center, New London, CT, 11 January 1984.
14. P. R. Bannister, Connecticut ELF Field Strength Measurements, August to December 1977 and July to September 1978, NUSC Technical Report 7357, Naval Underwater Systems Center, New London, CT (in press).
15. P. R. Bannister, Comparisons of 76-Hz Vertical Electric And Horizontal Magnetic Field Strengths Received in Connecticut, NUSC Technical Report 7369, Naval Underwater Systems Center, New London, CT (in press).
16. P. R. Bannister and F. J. Williams, "Results of the August 1972 Wisconsin Test Facility Effective Earth Conductivity Measurements," Journal of Geophysical Research, vol. 79, no. 5, 1974, pp. 725-732 (corrections listed in vol. 79, no. 17, 1974, p. 2698).
17. P. R. Bannister, A Compilation of Field Strength Formulas for ELF Radio Wave Propagation in the Earth-Ionosphere Waveguide, NUSC Technical Report 7521, Naval Underwater Systems Center, New London, CT (in press).
18. J. Galejs, Terrestrial Propagation of Long Electromagnetic Waves, Pergamon Press, NY, 1972.
19. M. L. Burrows, ELF Communications Antennas, Peter Peregrinus, Ltd., Stevenage, England, 1978.
20. P. R. Bannister, "Summary of the Results of the Wisconsin Test Facility Phasing Anomaly Investigations," Radio Science, vol. 13, no. 5, 1978, pp. 687-692.
21. P. R. Bannister, "The Determination of Representative Ionospheric Conductivity Parameters for ELF Propagation in the Earth-Ionosphere Waveguide," Radio Science, vol. 20, no. 4, 1985, pp. 977-984.
22. P. R. Bannister, "Variations in Extremely Low Frequency Propagation Parameters," Journal of Atmospheric and Terrestrial Physics, vol. 34, no. 9, 1975, pp. 1203-1210.
23. J. R. Wait, Electromagnetic Waves in Stratified Media, Pergamon Press, NY, 1970.
24. J. R. Wait and K. P. S. Spies, Characteristics of the Earth-Ionosphere Waveguide for VLF Radio Waves, NBS Technical Note 500, National Bureau of Standards, Boulder, CO, 1964.

INITIAL DISTRIBUTION LIST

Addressee	No. of Copies
DARPA	3
DTIC	15
ONR (Code 425GG (J. Heacock), 42810 (R. G. Joiner)	2
ASN (T. P. Quinn (for C ³), H. Hull (Rm SE 779)	2
NRL (Library, Dr. J. R. Davis (Code 7550), Dr. Frank Kelly)	3
NOSC (Library, R. A. Pappart, D. G. Morfitt, J. A. Ferguson, J. Bickel, F. P. Snyder, C. F. Ramstedt, P. Jansen, K. Grauer, W. Hart)	10
NAVELECSYSCOM (PME 110-11 (Dr. G. Brunhart), PME 110-X1 (Dr. Bodo Kruger), PME 110)	3
NAVAL SURFACE WEAPONS CENTER, WHITE OAK LAB. (J. J. Holmes, P. Wessel, K. Bishop, R. Brown, J. Cunningham, B. DeSavage, Library)	7
DWTNSRDC ANNA (W. Andahazy, F. E. Baker, P. Field, D. Everstine, B. Hood, D. Nixon)	6
NAVPGSCOL, MONTEREY (O. Heinz, P. Moose, A. Ochadlik, M. Thomas, W. M. Tolles, Library)	6
NCSC (K. R. Allen, R. H. Clark, M. J. Wynn, M. Cooper, E. Moritz, Library)	5
DIRECTOR, DEFENSE NUCLEAR AGENCY, RAAE, DDST, RAEV R&D Associates, P. O. Box 9695, Marina del Rey, CA 90291 (C. Greifinger, P. Greifinger)	3
Pacific-Sierra Research Corp., 12340 Santa Monica Blvd. Los Angeles, CA 90025 (E. C. Field)	2
Johns Hopkins University, Applied Physics Laboratory, Laurel, MD 20810 (L. Hart, J. Giannini, H. Ko, I. Sugai)	1
University of California, Scripps Institute of Oceanography (C. S. Cox (Code A 030), H. G. Booker, J. Filloux, P. Young)	4
Lockheed Palo Alto Research Laboratory (W. Imhof, J. B. Reagan, E. E. Gaines, R. C. Gunton, R. E. Meyerott)	5
University of Texas, Geomagnetics and Electrical Geoscience Laboratory (F. X. Bostick, Jr.)	5
COMMANDER, AIR FORCE GEOPHYSICS LABORATORY (J. Aarons)	1
COMMANDER ROME AIR DEVELOPMENT CENTER (J.P. Turtle, J. E. Rasmussen, W. I. Klemetti, P. A. Kossey, E. F. Altschuler)	1
Applied Science Associates, Inc. (Dr. Gary S. Brown) 105 E. Chatham St., Apex, NC 27502	1
Computer Sciences Corp., Falls Church, VA 22046 (D. Blumberg, Senator R. Mellenberg, R. Heppe, F. L. Eisenbarth)	4
MIT Lincoln Labs. (M. L. Burrows, D. P. White, D. K. Willits, S. L. Bernstein, J. F. Lutz)	5

INITIAL DISTRIBUTION LIST (Cont'd)

Addressee	No of copies
Electromagnetic Sciences Lab. SRI International, Menlo Park, CA 94015 (Dr. David M. Bubenik)	1
Communications Research Centre (Dr. John S. Belrose) P.O. Box 11490, Station "H" Shirley Bay, Ottawa, Ontario, Canada K2H8S2	1
Dr. Joseph P. deBettencourt, 18 Sterling St., West Newton, MA 02165	1
Dr. Marty Abromavage, IITRE, Div. E., 10W 35th St., Chicago, IL 60616	1
NDRE, Division for Electronics (Dr. Trygve Larson) P. O. Box 25, Kjeller, Norway	1
Belden Corp., Technical Research Center Mr. Douglas O'Brien) Geneva, Illinois	1
University of Pennsylvania (Dr. Ralph Showers) Moore School of Elec. Eng., Philadelphia, PA 19174	1
University of Houston, Director, Dept. of Elec. Eng. (Prog. Liang C. Shen)	1
The University of Connecticut, Physics Dept., (Prof. O. R. Gilliam) Storrs, CT 06268	1
Dr. David J. Thomson, Defence Research Establishment Pacific, F.M.O., Victoria, B.C., Canada	1
Dr. Robert Hansen, Box 215, Tarzana, CA 91356	1
The University of Kansas, Remote Sensing Laboratory (Prof. R. K. Moore) Center for Research, Inc., Lawrence, Kansas	1
OT/ITS U.S. Dept. of Commerce (Dr. David A. Hill), Boulder, CO	1
Office of Telecommunications, Inst. for Telecommunications Services (Dr. Douglas D. Crombie, Director), Boulder, CO	1
University of Colorado, Dept. of Electrical Eng. (Prof. David C. Chang)	1
Dr. K. P. Spies, ITS/NTIA, U.S. Dept. of Commerce	1
The University of Connecticut, Dept. of Electrical Eng. & Computer Sci., Storrs, CT (Prof. Clarence Schultz, Prof. Mahmood A. Melehy)	2
Dr. Richard G. Geyer, 670 S. Estes St., Lakewood, CO	1
University of California, Lawrence Livermore Lab., (E. K. Miller, R. J. King)	3
Kings College, Radiophysics Group (Prof. D. Llanwyn Jones) Strand, London WC2R 2LS, England	1
Istituto di Elettrotecnica, Facoltà di Ingegneria (Prof. Giorgio Tacconi) Viale Combiasso 5, 16145 Genova, Italy	1
Université des Sciences de Lille (Prof. R. Gabillard), B. P. 36-59650 Villeneuve D'Ascq, Lille, France	1
Arthur D. Little, Inc., (Dr. A. G. Emslie, Dr. R. L. Lagace, R&D Div., Acorn Park, Cambridge, MA 02140	2

INITIAL DISTRIBUTION LIST (Cont'd)

Addressee	No of copies
University of Colorado, Dept. of Electrical Eng. (Prof. S. W. Maley)	1
University of Washington, EE Dept. (Prof. A. Ishimaru) Seattle	1
Dr. Svante Westland, Kiruna Geofysiska Institute, S981 01 Kiruna 1, Sweden	1
Dr. Harry C. Koons, The Aerospace Corp. P.O. Box 92957, Los Angeles, CA 90009	1
Dr. Albert Essmann, Hoogewinkel 46, 23 Kiel 1, West Germany	1
Glenn S. Smith, School of Elec. Eng. Georgia Tech. Atlanta, GA	1
Dr. T. Lee, CIRCS, Campus Box 449, University of Colorado	1
Dr. Jack Williams, RCA Camden, Mail Stop 1-2, Camden, NJ 08102	1
Mr. Arnie Farstad, 390 S. 69th St., Boulder, CO 80303	1
NATO SACLANT ASW CENTER (Library)	1
USGS, Branch of Electromagnetism and Geomagnetism (Dr. James Towle) Denver, CO	1
NOAA, Pacific Marine Environ. Lab. (Dr. Jim Larsen)	1
University of Texas at Dallas, Geosciences Div. (Dr. Mark Landisman)	1
University of Wisconsin, Lewis G. Weeks Hall, Dept. of Geology and Geophysics (Dr. C. S. Clay)	1
Argonne National Laboratory, Bldg. 12 (Dr. Tony Valentino)	1
IITRE, Div. E, Chicago (Dr. Marty Abromavage)	1
The University of Manitoba, Elec. Eng. Dept. (Prof. A. Mohsen)	1
Mr. Jerry Pucillo, Analytical Systems, Engineering Corp., Newport, RI 02840	1
Dr. Misac N. Nabighian, Newmont Exploration Ltd., Tucson, AZ	1
Dr. Fred Raab, Green Mountain Radio Research Co., 50 Vermont Ave., Winooski, VT 05404	1
Dr. Louis H. Rorden, President, Develco, Inc.. 404 Tasman Dr., Sunnyvale, CA 94086	1
Dr. Eivind Trane, NDRE, P.O. Box 25, 2007 Kjeller, Norway	1
RCA David Sarnoff Research Center (K. Powers, J. Zennel, H. Staras)	4
University of Illinois, Aeronomy Laboratory (Prof C. F. Sechrist)	1
Dr. Cullen M. Crain, Rand Corp., Santa Monica, CA	1
Radioastronomisches Institute der Universitat Bonn (Dr. H. Volland), 5300 Bonn-Endenich, Auf dem Hügel 71, West Germany	1
Dr. John P. Wikswo, Jr., P.O. Box 120062 Acklon Station, Nashville, TN	1

INITIAL DISTRIBUTION LIST (Cont'd)

Addressee	No of copies
Mr. Lars Brock-Nannestad, DDRB Osterbrogades Kaserne, 2100 Copenhagen C, Denmark	1
Institut de Physique du Globe (Dr. Edouard Selzer) 11 Quai St., Bernard, Tour 24 Paris Ve, France	1
Elektrophysikalisches Institut (Dr. Herbvert Konig) Technische Hochschule, Arcisstrasse 21, 8 Munich 2, West Germany	1
Raytheon Company (Dr. Mario Grossi) Portsmouth, RI	1
NISC, Code OOW (Mr. M. A. Koontz) Washington, DC	1
Polytechnic Institute of Brooklyn (Prof. Leo Felsen)	1
NOAA/ERL (Dr. Earl E. Gossard) R45X7, Boulder, CO 80302	1
Dr. George H. Hagn, SRI-Washington, Rosslyn Plaza, Arlington, VA	1
NOAA/ERL (Dr. C. Gordon Little) R45 Goddard Space Flight Ctr. (Dr. S. J. Durrani) Code 800.1	1
ITS, Office of Telecon (Dr. Ken Steele) Boulder, CO 80302	1
NTIA/ITS, U.S. Dept. of Commerce (Dr. A. D. Spaulding)	1
Stanford University, Elec. Eng. Dept. Dr. O. G. Villard, Jr.)	1
Dr. D. Middleton, 127 East 91st St., New York, NY 10028	1
University of California, Elec. Eng. & Computer Sci. Dept., Prof. K. K. Mei)	1
California Inst. of Technology, Jet Propulsion Lab., (Dr. Yahya Rahmat-Samii)	1
Mr. Larry Ball, U.S. Dept. of Energy NURE Project Office, P.O. Box 2567, Grand Junction, CO 81502	1
STATE DEPARTMENT ACDA MA-AT, Rm. 5499, Washington, DC 20451 (ADM T. Davies, R. Booth, N. Carrera)	3
GTE Sylvania, (R. Row, D. Boots, D. Esten) 189 Broad St., Needham, MA 02194	3
HARVARD UNIVERSITY, Gordon McKay Lab. (Prof. R. W. P. King, Prof. T. T. Wu)	2
University of Rhode Island, Dept. of Electrical Engineering (Prof. C. Polk)	1
University of Nebraska, Electrical Engineering Dept., (Prof. E. Bahar)	1
University of Toronto, EE Dept. (Prof. Keith Balmain)	1
NOAA/ERL (Dr. Donald E. Barrick	1
University of Colorado, EE Dept. (Prof. Peter Beckmann)	1
Geophysical Observatory, Physics & Eng. Lab. DSIR Christchurch, New Zealand (Dr. Richard Barr)	1

INITIAL DISTRIBUTION LIST (Cont'd)

Addressee	No of copies
General Electric Co., (C. Zierdt, A. Steinmayer) 3198 Chestnut St., Philadelphia, PA 19101	2
University of Arizona, Elec. Eng. Dept., Bldg. 20 (Prof. J. R. Wait) Tuscon, AZ 85721	1
U.S. NAVAL ACADEMY, Dept. of Applied Science (Dr. Frank K. Chi)	1
Stanford University, Radioscience Laboratory (Dr. Anthony Fraser-Smith) Durand Bldg. Rm. 205	1
Stanford University, Stanford Electronics Laboratory (Prof. Bob Helliwell)	1
Colorado School of Mines, Department of Geophysics (Prof. A. Kaufman)	1
Prof. George V. Keller, Chairman, Group Seven, Inc., Irongate II, Executive Plaza, 777 So. Wadsworth Blvd, Lakewood, CO 80226	1
MIT, Dept. of Earth/Planetary Sciences, Bldg. 54-314 (Prof. Gene Simmons)	1
Colorado School of Mines (Dr. C. Stoyer)	1
University of Victoria, (Prof. J. Weaver) Victoria, B.C. V8W 2Y2 Canada	1
Mr. Donald Clark, c/o Naval Security Group Command, 3801 Nebraska Ave., NW, Washington, DC 20390	1
Prof. R. L. Dube, 13 Fairview Rd., Wilbraham, MA 01095	1
U.S. Geological Survey, Rm. 1244 (Dr. Frank C.Frischknecht) Denver, CO 80225	1
Mr. Larry Ginsberg, Mitre Corp., 1820 Dolly Madison Bldg. McLean, VA 22102	1
Dr. Robert Morgan, Rt. 1, Box 187, Cedaredge, CO 81413	1
Mr. A. D. Watt, Rt 1, Box 183 1/2, Delaredge, CO 81413	1
Dr. E. L. Maxwell, Atmospheric Sciences Dept., Colorado State University, Fort Collins, CO	1
Mr. Al Morrison, Purvis Systems, 3530 Camino Del Rio North, Suite 200, San Diego, CA 92108	1
Raytheon Service Co. (Dr. M. Soyda) Mt. Laurel NJ 08054	1
MITRE M/S W761 (Dr. W. Foster) McLean, VA	1
Max-Planck-Institut fur Aeromornie (Prof. P. Stubbe) 3400 Katlenburg-Lindau 3 FRG	1
University of Otago, Physics Dept. (Prof. R. L. Dowden) Dunedin, New Zealand	1
University of Leicester, Physics Dept. (Prof. T. B. Jones) Leicester, England	1
Naval Weapons Center, China Lake, Code 3814 (Dr. R. J. Dinger)	1
Dr. Claudia D. Tesche, Lutech, Inc., P.O. Box 1263, Berkeley	1
National Aeronautical Est., National Research Council, Flight Research Lab., (Dr. C. D. Harwick) Ottawa, K1AOR6, Canada	1

INITIAL DISTRIBUTION LIST (Cont'd)

Addressee	No of copies
Colorado Research and Prediction Laboratory, Inc. (Dr. R. H. Doherty, Dr. J. R. Johler) Boulder, CO	2
Arizona State University, School of Engineering, Dept. of Electrical and Computer Engineering (Prof. Constantine A. Balanis), Tempe, AZ 85287	1
University of Massachusetts, Dept. of Electrical and Computer Engineering, (Prof. Robert E. McIntosh), Amherst, MA 01003	1
Cairo University, Faculty of Engineering Electronics & Comm. Dept., (Dr. Samir F. Mahmond) Giza, Egypt	1
Virginia Polytechnic Institute and State University, Dept. of Electrical Engineering, (R. Clark Robertson), Blacksburg, VA 24061	1
NISC 52, (B. Blackburn), 4301 Smithland Road, Washington, DC 20390	1
University of Michigan Radiation Laoratory, Dept. of Electrical and Computer Engineering (Prof. Dikpa Sengupta), 4072 East Engineering Bldg., Ann Arbor, MI 48109	1
U-157, Elec. Eng. and Computer Sci. Dept., (Prof. Rajeer Bansal), UCONN, Storrs, CT 06268	1
Helsinki University of Technology, Dept. of Electrical Engineering, (I.V. Lindell & E. Alanen), Otakaari 5A, SF-021150 Espoo, Finland	1

E U D

D T C

8 - 86